



CUSHMAN®

SHUTTLE™ 6



TRANSPORT LARGE GROUPS EFFICIENTLY.

The Cushman® Shuttle™ 6 is your go-to vehicle for effectively moving people. With the combination of four-forward-facing seats and two rear-facing seats, you can safely transport up to six people comfortably throughout your facility. Available with the option of an energy efficient 72V AC electric drivetrain or a 13.5 HP Kawasaki® gas engine, the Shuttle 6 has the stamina necessary to take care of your personnel.

LET'S WORK.®

13.5HP
KAWASAKI®
GAS ENGINE
OPTION

72V
AC ELECTRIC
DRIVETRAIN
OPTION

6
PERSON
SEATING
CAPACITY



CUSHMAN® SHUTTLE™ 6



HEADLIGHTS



BENCH SEATING

RACK-AND-PINION
STEERING

OPTIONS & ACCESSORIES

- Rearview Mirror
- Windshield
- Canopy
- Hour Meter
- Individual Key Switch
- Pinstripes
- Body Color (Forest Green, White or Custom Options)
- On Board Charger
- Turn Signal with Four-Way Flashers
- Brakelights
- LED Headlights
- CE Kit (gas only)
- Wheel Covers - Spoke and Chrome
- Limited Slip Differential
- Trail Tires



COVERED WITH THE 2-YEAR CUSHMAN CARE TOTAL PROTECTION WARRANTY

ELECTRIC MODEL

GAS MODEL

BODY & CHASSIS	
FRAME	Welded Steel w/ DuraShield™ Powder Coat
BODY & FINISH	Injection Molded TPO
STANDARD COLOR	Ivory
DIMENSIONS	
OVERALL LENGTH	136.0 in (345 cm)
OVERALL WIDTH	48.5 in (123 cm)
OVERALL HEIGHT	48.6 in (123 cm) (w/o Roof) / 72.0 in (183 cm) (w/ Struts & Roof)
WHEEL BASE	93.5 in (237 cm)
WHEEL TRACK	34.2 in (87 cm) Front / 38.0 in (97 cm) Rear
GROUND CLEARANCE	4.3 in (11 cm)
POWER	
POWER SOURCE	72V DC
VALVE TRAIN	22.4 hp (16.7 kW) Intermittent
HORSEPOWER (KW)	72V
ELECTRICAL SYSTEM	Six, 12 Volt Deep Cycle
BATTERY CHARGER	1000 Watt, 72V, 120/230V VAC UL Listed
KEY OR PEDAL START	Pedal
AIR CLEANER	N/A
LUBRICATION	N/A
OIL FILTER	N/A
COOLING SYSTEM	N/A
FUEL CAPACITY	N/A
SPEED CONTROLLER	350 Amp AC
DRIVE TRAIN	Motor Shaft Direct Drive
TRANSAXLE	Differential w/ Helical Gears
GEAR SELECTION	Dash-Mounted Forward-Neutral-Reverse
REAR AXLE RATIO	17:1
PERFORMANCE	
SEATING CAPACITY	6-Person
WEIGHT W/O BATTERIES	964 lb (437 kg)
CURB WEIGHT	1456 lb (660 kg)
VEHICLE LOAD CAPACITY	1200 lb (544 kg)
OUTSIDE CLEARANCE CIRCLE	25.5 ft (7.8 m)
SPEED	16.5 mph ± 0.5 mph (26.4 kph ± 0.8 kph) (High Speed) 12 mph ± 0.5 mph (19.3 kph ± 0.8 kph) (Low Speed)
STEERING & SUSPENSION	
STEERING	Self-Compensating Rack & Pinion
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical, Self-Adjusting Drum
PARKING BRAKE	Self-Compensating, Single-Point Engagement
TIRES (FRONT & REAR)	Hole-N-One 18 x 8.50 - 8 (4 Ply Rated)

www.cushman.com

©2018 Textron Specialized Vehicles Inc.
Features and specifications of the vehicles are subject to change without notice.
Vehicle as photographed may include options not included on base model.

82284-G6 (Rev. 08/2018)